



BASIC expansion tank		60 L	115 L	150 L	230 L	300 L	450 L
Tank volume	gal	16	30	40	60	80	119
	liter	60	115	150	230	300	450
Inner diameter	inch	18	18	18	24	24	24
	mm	460	460	460	610	610	610
Weight	kg	9,9	12,9	14,8	19,8	22,8	32,6
Total height	inch	25,59	38,38	48,03	42,13	51,77	71,85
	mm	650	975	1220	1070	1315	1825
Bottom of the tank (type 1)	1 opening 160 mm with V-clamps and 1 tube 5/4"						
Top of the tank	Air valve						

OPTIONS

Bottom lid with 2 openings and 2 tubes 5/4" (type 2)

Flow through bottom lid with 2 openings and 2 tubes 5/4" (type 3)



SIDEHOLE expansion tank		115 L	150 L	230 L	300 L	450 L
Tank volume	gal	30	40	60	80	119
	liter	115	150	230	300	450
Inner diameter	inch	18	18	24	24	24
	mm	460	460	610	610	610
Weight	kg	13	15	20	23	32,7
Total length	inch	35,24	44,88	36,19	47,83	67,91
	mm	895	1140	970	1215	1725

OPTIONS

Brass tank outlet 28 mm

Plastic push-fit elbow 28 mm

Brass male coupler m28 x 1"

Galvanised support set 18" or 24"

Characteristics

Min. ambient & water temperature	1°C / 34°F
Max. ambient & water temperature	50°C / 120°F
Air cell preset pressure by manufacturer	1,5 bar / 21,76 psi / 150 kpa
Maximum pressure air cell	3 bar / 43,52 psi / 300 kpa
Maximum design pressure	8 bar / 116 psi / 800 kpa
Bladder	TPU
Barrier tank	PBI
Reinforcement layer	GF/PP